



MP-6S-C-1 | 6-2111989-3

Modular Plug Kit, category 6, shielded, 8-position, 5.7 – 7.0 mm max cable jack OD, 100/bag

Body Features

Conductor Type	Solid Stranded
Shield Material	Stainless steel
Shield Plating Material	Nickel

Configuration Features

Number of Positions	8
Keyed	No

Contact Features

Contact Base Material	Phosphor bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.00 μ m 1.27 μ m
Number of Contacts Loaded	8

Dimensions

Cable Jacket Outside Diameter Range	0.224–0.276 in 5.7–7.0 mm
Conductor Wire Size	26–23 AWG
Insulated Conductor Outside Diameter	0.035–0.043 in 0.89–1.09 mm

Housing Features

Housing Material	Glass filled polycarbonate
------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 1863
------------------------	---------

Packaging Features

Packaging Quantity	100
--------------------	-----

Product Availability

Region	Asia Australia/New Zealand EMEA Latin America North America
--------	---

Product Type Features

Cable Type	Round, shielded
Performance Category	Category 6
Connector Style	Plug
Jack Type	RJ45

MP6SC-1 | 6-2111989-3

Latch Style	Standard
Product Type	Connector
Shielded	Yes
System	AMP NETCONNECT

Termination Features

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
----------------------------------	-------------------------------------