

## **6979ST DVB-S2 DVB-T2 衛星 dB 錶**

4.3 Inch High Definition TFT LCD Screen

Fully DVB-S/S2/T/T2, MPEG-2/MPEG4 compliant

MPEG-2 / H.264 Hardware decoding

Digital meter for signal strength and quality

Constellation analyzer

Spectrum analyzer

Supports scan of Auto,Blind,Manual or NIT

Sound and Light Alarm for Locking Signal

Auto Calculate Angle of AZ ,EL

Supports DISEQC 1.0/1.1/1.2 ,0/22khz Tone

Speaker Integrated

Support both AV out and AV in

LNB short protect

7.4V/3000mAh Li-Ion Battery Included

Software upgrade via USB port

Easy to carry

One Herts Digital Videotech Co., Ltd.

Tel : +886-7-555-5959

Fax : +886-7-552-5977

<http://www.oneherts.com.tw>

e-mail:oneherts@yahoo.com.tw

## Front of indicator picture



## Back of indicator picture



System capabilities	Fully DVB compliant	Yes
SATELLITE INPUT/ DEMODULATION	Connector Type	F Type
	Input Frequency	950 to 2150 MHz
	Signal Input Level	- 65 to -25 dBm
	LNB Supply	13V/18V, IMax 400mA
	Demodulation Type	QPSK,8PSK,16APSK
	Symbol Rate	2<Rs<45Mband(SCPC/MCPC)
DVB-S/S2 Input /Demodulation	Connector Type	FEMALE Type
	Input Frequency	48 to 862 MHz
	Signal Input Level	-79.5dBm (MAX)
	ANT Supply	5V, 12V/17V Imax 100mA
	Demodulation Type	QPSK,16QAM,64QAM,256QAM
LCD Features	LCD Type	TFT TRANSMISSIVE
	Number of Dots	480(RGB) x272
	Active area (W x H)	95.04x53.86 mm <sup>2</sup>
AV Output interface	Connector Type	3.5 mm jack
	Video Output	CVBS
	Audio Output	Stereo Audio L/R output
HDMI output connector	Format	HDMI 1.3a
AV Input interface	Connector Type	3.5 mm jack
	Video input	CVBS
	Audio input	Stereo Audio L/R input
Audio/Video Processing	Resolving rate	PAL-25 frame@720*576,NTSC-30 frame@720*480,
	Signal compatibility	Support conversion for different video formats
	Video Format	4:3,16:9,By Pan & Scan and Letter Box conversion
	Audio output mode	Stereo, Mono, R/L
Data Service Port	Connector	USB
	Data protocol	USB2.0 interface
	File format	wma,mp3,mp4,avi,jpg,jpeg,bmp,img
Microprocessor	Microprocessor	NOVATEK
	Clock Frequency	500MHz
	SDRAM Memory	1Gbit DDR3
Power Supply	Li-Ion Battery	7.4V/3000mAh(The machine behind labeling shall prevail)
	Adapter	OUTPUT :DC12V/1.5A INTUPT :100-240V AC 50/60Hz(Will be subject to actual configuration)
	Power consumption	Max. 10W
Physical Characerstics	Size	125x205X45(mm)
	Net Weight	0.66KG

One Herts Digital Videotech Co., Ltd.

Tel : +886-7-555-5959

Fax : +886-7-552-5977

<http://www.oneherts.com.tw>

e-mail:oneherts@yahoo.com.tw

## Standard Accessories



Car Charger Cable  
1/pc



AV Cable  
1/pc



Power Adaptor  
1/pc



Carrying bag  
1/pc

## Optional Accessories