



CATV DISTRIBUTION AMPLIFIER

WCA-5086

Features

- Deluxe Aluminum Housing for Excellent Head-Sinking
- 60 dBmV High Output Level
- -20 dB Input/Output Test Point
- Tilt Control & Gain Control Continuously Adjustable
- Built-in Power Supply for Easy Installation

Specifications

Operation Freq. Range	: 45~860 MHz
Output Level	: 60 dBmV
Gain	: Typical 50 dB
Gain Control	: 0~-18 dB adjustable
Tilt Control	: 0~-16 dB adjustable
Gain Flatness	: ± 1.0 dB
Input Return Loss	: ≥ 13 dB
Output Return Loss	: ≥ 14 dB
Noise Figure	: 7.0 dB
Input & Output Impedance	: 75 Ω
Input & Output Test Point	: -20 dB
Connector	: All F-Type
Power Supply	: 100V~120V AC or 190~230V AC
Power Consumption	: 20W
Operating Temperature	: -10~+60°C
AC Fuse(Internal)	: 1 Amp
Dimension	: 220mm (L) x 110mm (W) x 50 mm (H)
Packing	: 10 pcs/Carton/16.5Kgs/1.82 cuft

One Herts Digital Videotech Co., Ltd.

No.23, Huaning Rd., Gushan Dist., Kaohsiung City 804, Taiwan (R.O.C.)

Tel : +886-7-555-5959 / Fax : +886-7-552-5977

E-mail:oneherts.com.tw / Line ID:@h5959